

ENVIRONMENTAL PRODUCT DECLARATION

In accordance with ISO 14025 and EN 15804+A2



Komproment ApS Saga 400 Auburn Brown



Komproment
wienerberger

Owner of the declaration

Komproment ApS
21 Porsborgparken
9530 Støvring
Denmark

Product

Saga 400 Auburn Brown

Declared product / Declared unit

1 m²

This declaration is based on Product Category Rules

EN 15804:2012 + A2:2019,
NPCR Part A:2021 ,
NPCR 022 Part B for Roof Waterproofing

Program operator:

EPD Global
Majorstuen P.O. Box 5250
N-0303 Oslo
Norway

Declaration number

NEPD-30044-30044-2

Registration number

NEPD-30044-30044-2

Issue date

22.10.2026

Valid to

21.10.2031

EPD Software

Emidat Platform v1.0.0

General Information

Product

Saga 400 Auburn Brown

Program Operator

EPD Global
Majorstuen P.O. Box 5250
N-0303 Oslo
Norway
Phone: +47 23 08 80 00
Email: post@epd-norge.no

Declaration Number

NEPD-30044-30044-2

This declaration is based on Product Category Rules

EN 15804:2012 + A2:2019,
NPCR Part A:2021 ,
NPCR 022 Part B for Roof Waterproofing

Statements

The owner of the declaration shall be liable for the underlying information and evidence. The Norwegian EPD Foundation shall not be liable with respect to manufacturer, life cycle assessment data and evidences.

Declared unit

1 m²

General information on verification of EPD from EPD tools

Independent verification of data, other environmental information and the declaration according to ISO 14025:2011-10, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD Global's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD Global, and iii) the process is reviewed annually by an independent third-party verifier. See Appendix G of EPD Global's General Programme Instructions for further information on EPD tools.

Verification

Independent third-party verification based on the verification of the EPD tool, background data and test-EPD in accordance with EPD Global's procedures and guidelines for verification and approval of EPD tools.
Third-party verifier: Charlotte Merlin, FORCE Technology

Owner of the declaration

Komproment ApS

Contact person

Salg@komproment.dk

Phone

+45 96 52 07 10

Email

Salg@komproment.dk

Manufacturer

Komproment ApS
21 Porsborgparken
9530 Støvring, Denmark

Place of production

Križevci pri Ljutomeru, Slovenia

Management system

-

Organisation no

DK25043499

Issue date

22.10.2026

Valid to

21.10.2031

Year of study

2025

Comparability

EPDs of construction products may not be comparable if they do not comply with EN 15804 and are not seen in a building context. EPD data may not be comparable if the datasets used are not developed in accordance with EN 15804 and if the background systems are not based on the same database (including primary and secondary data).

Development and verification of EPD

The declaration was created using the Emidat EPD tool v1.0, developed by Emidat GmbH which is third-party verified and approved as a Reference Flow Tool with internal review under administration and surveillance by EPD Global under provisions stated in general information on verification of EPD from EPD tools.

Developer of EPD: Helene Frey

Reviewer of company-specific input data and EPD: Kristian Knorr Svane

Approved



Håkon Hauan, The Norwegian EPD Foundation

Product

Product description

Clay tiles are durable, modular construction units made primarily from clay and sand. Variations in clay type, pigments, and forming processes result in varied aesthetics.

This EPD specifically covers Auburn Brown Saga 400U and 400L clay tiles.

The declared unit of 1 m² includes the headlap, as installed with vertical gauge of 145 mm.

Application description

Clay tiles are typically used as façade cladding in combination with a mounting system.

Guidance for installation

The product is suitable for use as a discontinuous roof covering on pitched roofs in accordance with EN 1304 and the applicable national application standards and codes of practice. The tiles are laid overlapping on battens, with roof pitch and mechanical fixing according to exposure conditions. For product-specific installation details and current usage recommendations, the user is referred to the manufacturer's installation documentation.

Production process



Product specification

Name of ingredient	Share of total weight
Clay	90 - 100 %
Composite	0 - 2 %

Packaging

Name	Quantity, kg
Wooden pallets	1.12
Softwood	0.02
PET	0.01
Cardboard	8.26e-03
LDPE	0.03

Technical data

	Unit	Value
Coverage	tiles / m ²	17
Weight per tile	kg	2.3
Thickness	mm	14

The product is produced according to the harmonized standard EN 1304.

Market

Europe

Recipients

B2B

LCA: Calculation rules

Declared unit

1 m²

Product lifetime


60 years

This value represents a conventional product lifespan, not a guaranteed performance duration, and assumes normal exposure conditions, adequate design, and routine maintenance.

Reference service life

Not declared

System boundary



Data quality

The foreground data are based on extensive and detailed data collection at the production site of the manufacturer, covering key processes such as raw material sourcing, formulation, and manufacturing. These foreground data are fully linked with corresponding datasets from the background database (ecoinvent 3.10) or with EN15804+A2-compliant EPDs, ensuring consistency, reliability, and maintaining alignment with the latest industry standards.

The overall data representativeness is rated as good with an overall score of 4.00/5, in accordance with EN 15804+A2 Annex E guidance on data quality assessment for the calculation of the environmental footprint of products (Table E.2), considering geographical, technical, and temporal representativeness.

The following table discloses all processes or activities assessed with very poor or poor data representativeness according to EN 15804+A2, as well as those assessed as fair that contribute more than 30 % to any core impact indicator in A1–A3:

Element	Source	Year
Clay	ecoinvent 3.10	2023
Composite	ecoinvent 3.10	2023
Incineration	ecoinvent 3.10	2023
Landfill	ecoinvent 3.10	2023
Manufacturing fuels	ecoinvent 3.10	2023
Recycling	ecoinvent 3.10	2023

System boundaries (X=included, MND=module not declared)

	Production			Installation		Use stage							End-of-Life				Next product system
	Raw material supply	Transport	Manufacturing	Transport	Installation Process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational Energy Use	Operational Water Use	Demolition	Transport	Waste Processing	Disposal	Benefits and loads beyond the system boundary
Module	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	x	x	x	x	x	MND	MND	MND	MND	MND	MND	MND	x	x	x	x	x
Geography			SI	Europe	Europe	MND	MND	MND	MND	MND	MND	MND	Europe	Europe	Europe	Europe	Europe

For the geographies modeled in A1 and A2, refer to *Product specification*.

Type of EPD: Cradle to gate with options, modules A4, A5, C1-C4 + D

Product and construction stage

Module A1: Extraction and processing of raw materials

Module A2: Transportation of raw materials to the plant

Module A3: Clay tiles production at the plant and waste treatment

Module A4: Transportation to the construction site

Module A5: Installation of clay tiles and installation losses

Disposal Stage

Module C1: Demolition/Dismantling

Module C2: Transportation of demolition waste for processing

Module C3: Treatment of waste

Module C4: Final disposal

Credits and burdens outside the system boundaries

Module D: Environmental credits from recycling

Cut-off criteria

All inputs and outputs related to the declared modules of Clay tile, including raw materials, packaging, transportation, energy usage and ancillary materials, were comprehensively considered in line with EN 15804+A2 and if applicable the product-specific PCR. Furthermore, all known hazardous substances (within the REACH list and the Norwegian Priority List), regulated materials, and significant emissions were declared and are not excluded under the cut-off rules.

The following processes are considered below the EN 15804+A2 cut-off threshold and were excluded:

- Impacts related to the manufacturer's infrastructure and assets
- Manufacturing of means of production, buildings or other capital goods
- Transportation of personnel to the plant
- Transportation of personnel within the plant
- Research and development activities
- Long-term emissions

Allocation

Foreground inventory data (energy and fuels, ancillary materials, emissions and waste) was collected at the production process level. Allocation based on mass was applied to allocate the total output of the production process in 2025 to the reference product.

Key assumptions and estimates

Production process flows are allocated to the reference product, as described under allocation. If applied, mass-based allocation assumes a uniform distribution of production impacts across products of the same production process. Where it is applied, foreground inventory data is checked for consistency of production process, to ensure the validity of the allocated results.

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD. Mass and energy flows are reported per 1 m² of product.

Transport to the building site (A4)	Value	Unit
Location of the production site	Slovenia	
Location of the installation site	Europe	
Transported mass: Product and packaging	40.29	kg
Transport modality: Truck	transport, freight, lorry >32 metric ton, EURO6	-
Distance	1910.00	km
Litres of fuel	36.48	l / 100km
Energy demand	1.58	MJ / t*km
Energy demand (km)	0.06	MJ / km
Capacity utilization	53.30	%

Transport of the product and its packaging from the production site to the installation site. Transport distances are primary data provided by the manufacturer. Vehicle type, fuel consumption and capacity utilization assumptions stem from the underlying background transport datasets and are stated below.

Installation into the building (A5)	Value	Unit
Ancillary materials for installation		
Steel screws	0	kg
Bituminous primer	0	kg
Sealing tape	0	kg
Galvanized steel profile	0	kg
Lap sealant	0	kg
Flashing strip	0	kg
Water use during installation	0	m ³
Use of other resources during installation	0	kg
Energy consumption during installation		
Diesel for installation equipment	0	l
Material waste on the construction site before waste processing		
Wooden pallets	1.12	kg
Softwood	0.02	kg
PET	0.01	kg
Cardboard	8.26e-03	kg
LDPE	0.03	kg
Installation loss rate	5.00	%
Installation loss amount	1.95	kg
Direct emissions to ambient air, soil and water	0	kg
Treatment of packaging waste	Wooden pallets	

Installation into the building (A5)	Value	Unit
Reuse	100.00	%
Treatment of packaging waste	Softwood	
Landfill	32.00	%
Recycling	38.00	%
Incineration	30.00	%
Treatment of packaging waste	PET	
Landfill	23.00	%
Recycling	42.00	%
Incineration	35.00	%
Treatment of packaging waste	Cardboard	
Landfill	5.00	%
Recycling	87.00	%
Incineration	8.00	%
Treatment of packaging waste	LDPE	
Landfill	23.00	%
Recycling	42.00	%
Incineration	35.00	%
Treatment of installation loss waste		
Landfill	100.00	%

Installation losses are accounted for by scaling up the quantity of product required at the construction site by the loss percentage. The production, transportation and treatment of the lost material is assigned to A5. As installation is carried out manually, no installation energy use is included in module A5.

End-of-life scenario (C1-C4)	Value	Unit
Collection process specified by type		
Collected individually	0	kg
Collected with mixed construction and demolition waste	39.10	kg
Recovery system specified by type		
Destined for reuse	0	kg
Recycling rate	70.00	%
Destined for recycling	27.37	kg
Destined for energy recovery	0	kg
Disposal specified by type		
Product or material destined for final disposal	11.73	kg
Transport		
Distance to landfill	50.00	km
Distance to recycling	50.00	km
Transport modality: Truck	transport, freight, lorry >32 metric ton, EURO6	-
Energy demand	1.58	MJ / t*km

End-of-life scenario (C1-C4)	Value	Unit
Energy demand (km)	0.06	MJ / km
Capacity utilization	53.30	%

For the manual deconstruction of the product, no environmental impact is modeled. Module C2 includes the impact of transportation of material after deconstruction, during the End-of-Life stage.

Reuse, recovery and/or recycling potentials (D)	Value	Unit
Amount of secondary material that the system takes in	0	kg
Installation (packaging): Material for recycling/reuse	0.03	kg
Installation (packaging): Net flow of secondary material	0.03	kg
End-of-life (product): Material for recycling/reuse	27.37	kg
End-of-life (product): Net flow of secondary material	27.37	kg
Substitution of gravel	27.37	kg
Substitution of wood chips	9.41e-03	kg
Substitution of plastics	0.02	kg
Substitution of paper	7.18e-03	kg
Installation (packaging): Material eligible for incineration credits	0.02	kg
Installation (packaging): Exported energy eligible for credits	0.28	MJ
Installation (production loss): Material eligible for incineration credits	0	kg
Installation (production loss): Exported energy eligible for credits	0	MJ
End-of-life (product): Material eligible for incineration credits	0	kg
End-of-life (product): Exported energy eligible for credits	0	MJ
Substitution of electricity production, grid mix	0.08	MJ
Substitution of heat production from natural gas	0.20	MJ

Calculation of loads and benefits per EN 15804+A2. Exported energy is credited only where it originates from the incineration of primary material; landfilled fractions receive no exported-energy credit and therefore no avoided primary energy consumption. Recycling or reuse benefits are credited for the net flow of secondary material.

LCA: Results

The following results are based on the market-based electricity approach applied to the foreground system (A3). Further details on electricity data are provided in the Additional Requirements section.

Core environmental impact indicators

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-total	kg CO ₂ -eq.	8.42e+00	7.98e+00	2.77e+00	0.00e+00	2.03e-01	9.85e-02	6.91e-02	-7.36e-02
GWP-fossil	kg CO ₂ -eq.	1.03e+01	7.97e+00	9.82e-01	0.00e+00	2.02e-01	9.84e-02	6.91e-02	-6.88e-02
GWP-biogenic	kg CO ₂ -eq.	-1.86e+00	4.00e-03	1.79e+00	0.00e+00	1.02e-04	0.00e+00	0.00e+00	-4.61e-03
GWP-luluc	kg CO ₂ -eq.	2.09e-03	2.83e-03	2.63e-04	0.00e+00	7.19e-05	8.56e-06	1.11e-05	-1.19e-04
ODP	kg CFC-11-Eq	8.18e-07	1.66e-07	5.01e-08	0.00e+00	4.22e-09	1.51e-09	2.57e-09	-2.46e-09
AP	mol H ⁺ -Eq	2.45e-02	1.88e-02	2.31e-03	0.00e+00	4.78e-04	8.88e-04	4.30e-04	-7.17e-05
EP-freshwater	kg P-Eq	5.40e-04	5.61e-04	5.99e-05	0.00e+00	1.42e-05	2.87e-06	3.14e-06	-4.33e-05
EP-marine	kg N-Eq	1.03e-02	4.94e-03	8.21e-04	0.00e+00	1.25e-04	4.12e-04	1.84e-04	1.37e-04
EP-terrestrial	mol N-Eq	1.11e-01	5.34e-02	8.76e-03	0.00e+00	1.36e-03	4.51e-03	2.01e-03	9.56e-04
POCP	kg NMVOC-Eq	2.92e-02	3.27e-02	3.32e-03	0.00e+00	8.30e-04	1.35e-03	8.12e-04	2.64e-04
ADPE	kg Sb-Eq	2.12e-05	2.28e-05	2.32e-06	0.00e+00	5.79e-07	3.53e-08	8.80e-08	-1.72e-06
ADPF	MJ, net calorific value	2.13e+02	1.20e+02	1.72e+01	0.00e+00	3.04e+00	1.29e+00	1.72e+00	-1.88e+00
WDP	m ³ world Eq deprived	1.48e+00	6.01e-01	1.11e-01	0.00e+00	1.53e-02	3.15e-03	5.83e-03	-4.43e-01

GWP-total: Global Warming Potential - total , **GWP-fossil:** Global warming potential - fossil , **GWP-biogenic:** Global Warming Potential - biogenic , **GWP-luluc:** Global Warming Potential - luluc , **ODP:** Depletion potential of the stratospheric ozone layer , **AP:** Acidification potential, Accumulated Exceedance , **EP-freshwater:** Eutrophication potential - freshwater , **EP-marine:** Eutrophication potential - marine , **EP-terrestrial:** Eutrophication potential - terrestrial , **POCP:** Photochemical Ozone Creation Potential , **ADPE:** Abiotic depletion potential - non-fossil resources , **ADPF:** Abiotic depletion potential - fossil resources , **WDP:** Water (user) deprivation potential

Additional indicators

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PM	disease incidence	1.92e-07	7.76e-07	5.21e-08	0.00e+00	1.97e-08	2.29e-07	1.09e-08	2.10e-07
IRP	kBq U235-Eq	2.52e+00	1.45e-01	1.36e-01	0.00e+00	3.69e-03	5.76e-04	1.47e-03	-2.49e-02
ETP-fw	CTUe	1.23e+01	2.83e+01	2.23e+00	0.00e+00	7.20e-01	1.82e-01	1.76e-01	-1.08e+00
HTP-c	CTUh	2.31e-08	5.10e-08	3.89e-09	0.00e+00	1.30e-09	3.85e-10	2.90e-10	-2.14e-09
HTP-nc	CTUh	2.71e-08	7.89e-08	5.71e-09	0.00e+00	2.00e-09	1.75e-10	2.66e-10	-1.61e-09
SQP	dimensionless	1.97e+01	1.20e+02	7.87e+00	0.00e+00	3.06e+00	9.02e-02	3.48e+00	-4.40e+00

PM: Potential incidence of disease due to PM emissions , **IRP:** Potential Human exposure efficiency relative to U235 , **ETP-fw:** Potential Comparative Toxic Unit for ecosystems , **HTP-c:** Potential Comparative Toxic Unit for humans - cancer effects , **HTP-nc:** Potential Comparative Toxic Unit for humans - non-cancer effects , **SQP:** Potential Soil quality index . **IRP:** This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator. **ETP-fw, HTP-c, HTP-nc, SQP:** The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experienced with these indicators.

Use of resources

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PERE	MJ	2.82e+00	1.90e+00	4.02e-01	0.00e+00	4.82e-02	7.88e-03	3.52e-02	-5.53e-01
PERM	MJ	1.65e+01	0.00e+00	-1.55e+01	0.00e+00	0.00e+00	0.00e+00	0.00e+00	-2.63e-01
PERT	MJ	1.93e+01	1.90e+00	-1.51e+01	0.00e+00	4.82e-02	7.88e-03	3.52e-02	-8.16e-01
PENRE	MJ	2.11e+02	1.20e+02	1.77e+01	0.00e+00	3.04e+00	1.29e+00	1.72e+00	-1.11e+00
PENRM	MJ	2.63e+00	0.00e+00	-2.13e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	-7.64e-01
PENRT	MJ	2.14e+02	1.20e+02	1.56e+01	0.00e+00	3.04e+00	1.29e+00	1.72e+00	-1.88e+00
SM	kg	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	2.74e+01
RSF	MJ	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00
NRSF	MJ	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00
FW	m³	3.92e-02	1.74e-02	3.22e-03	0.00e+00	4.42e-04	8.36e-05	1.96e-03	-1.04e-02

PERE: Primary energy resources - renewable: use as energy carrier , **PERM:** Primary energy resources - renewable: used as raw materials , **PERT:** Primary energy resources - renewable: total , **PENRE:** Primary energy resources - non-renewable: use as energy carrier , **PENRM:** Primary energy resources - non-renewable: used as raw materials , **PENRT:** Primary energy resources - non-renewable: total , **SM:** Use of secondary material , **RSF:** Renewable secondary fuels , **NRSF:** Non-renewable secondary fuels , **FW:** Net use of fresh water

Waste flows

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
HWD	kg	2.39e-03	0.00e+00	1.20e-04	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00
NHWD	kg	2.84e-02	0.00e+00	2.00e+00	0.00e+00	0.00e+00	0.00e+00	1.17e+01	0.00e+00
RWD	kg	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00

HWD: Hazardous waste disposed , **NHWD:** Non hazardous waste disposed , **RWD:** Radioactive waste disposed

Output flows

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
CRU	kg	0.00e+00	0.00e+00	1.12e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00
MFR	kg	2.24e-02	0.00e+00	3.57e-02	0.00e+00	0.00e+00	2.74e+01	0.00e+00	0.00e+00
MER	kg	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00
EEE	MJ	2.04e-02	0.00e+00	8.07e-02	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00
EET	MJ	6.69e-02	0.00e+00	2.05e-01	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00

CRU: Components for re-use , **MFR:** Materials for recycling , **MER:** Materials for energy recovery , **EEE:** Exported electrical energy , **EET:** Exported thermal energy

Name	Value	Unit
Biogenic carbon content in product	0.00e+00	kg C
Biogenic carbon content in accompanying packaging	5.12e-01	kg C

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

Electricity consumption in the manufacturing phase is composed from the sources below. This EPD follows the market-based approach.

Approach	Electricity	Quantity [kWh]	Emission Factor [kg CO ₂ e/kWh]
market-based	ecoinvent: electricity production, nuclear, pressure water reactor (SI)	3.31	7.16e-03
(location-based)	(ecoinvent: market for electricity, high voltage (SI))	(3.31)	(0.34)

Rows marked with () are provided for reference and not used in the assessment.

Dangerous substances

The product contains no hazardous substances given by the REACH Candidate List or the Norwegian Priority List.

Additional environmental information

Secondary content

The product contains 0 % secondary material. Secondary material includes recycled, recovered and by-product content.

Additional environmental impact indicators required in NPCR Part A for construction products

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-IOBC	kg CO ₂ -eq.	1.03e+01	7.97e+00	9.84e-01	0.00e+00	2.03e-01	9.85e-02	6.91e-02	-6.88e-02

GWP-IOBC: Global Warming Potential - Instantaneous oxidation of biogenic carbon

Bibliography

CEN/TR 15941:2010	Sustainability of construction works - Environmental product declarations - Methodology for selection and use of generic data
EN 15804:2012+A2:2019	Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products
EN 15942:2022-04	Sustainability of construction works - Environmental product declarations - Communication format business-to-business
ISO 14025:2011-10	Environmental labels and declarations - Type III environmental declarations - Principles and procedures
ISO 14040:2021-02	Environmental management - Life cycle assessment - Principles and framework
ISO 14044:2021-02	Environmental management - Life cycle assessment - Requirements and guidelines
EF 3.1	Environmental Footprint (EF) Life Cycle Impact Assessment method - Characterisation Factors version 3.1, European Commission, Joint Research Centre (JRC)
ecoinvent 3.10	ecoinvent, Zurich, Switzerland, database version 3.10
NPCR Part A:2021	Construction products and services, Version 2.0. Issue date: 24.03.2021; validity extended to 31.12.2026.
NPCR 022:2022	Product category rules, Part B: Roof waterproofing, Version 2.0. Issue date: 31.03.2022; validity extended to 31.12.2026.
EN 17160:2019	Product category rules for ceramic tiles.

 epd-global <small>Powered by EPD-Norway</small>	Program Operator	Phone	+47 23 08 80 00
	EPD Global P.O. Box 5250 Majorstuen, N-0303 Oslo Norway	Email	post@epd-norge.no
		Web	www.epd-global.no
 epd-global <small>Powered by EPD-Norway</small>	Publisher	Phone	+47 23 08 80 00
	EPD Global P.O. Box 5250 Majorstuen, N-0303 Oslo Norway	Email	post@epd-norge.no
		Web	www.epd-global.no
 Komproment <small>© wienerberger</small>	Owner of the declaration	Phone	+45 96 52 07 10
	Komproment ApS 21 Porsborgparken, 9530 Støvring Denmark	Email	Salg@komproment.dk
		Web	Komproment.dk
 Komproment <small>© wienerberger</small>	Author of the life cycle assessment	Phone	+45 96 52 07 10
	Komproment ApS 21 Porsborgparken, 9530 Støvring Denmark	Email	Salg@komproment.dk
		Web	Komproment.dk
	ECO Platform	Web	www.eco-platform.org
	ECO Portal	Web	ECO Portal
 EMIDAT	Developer of EPD generator	Phone	+49 176 56 96 77 91
	Emidat GmbH Sandstraße 33, 80335 München Germany	Email	epd@emidat.com
		Web	www.emidat.com